



CF FLANGED CLAMPS ONE PART

PART NO	RANGE	Size, Length, Bolts	FL Drilled "D"		
			3"	4"	6"
			80mm	100mm	150mm
CF1-0375-16 x FL	95 - 104	M12 X 400 X 4	✓		
CF1-0440-16 x FL	104 - 111	M12 X 400 X 4	✓		
CF1-0450-16 x FL	113 - 120	M16 X 400 X 4	✓	✓	
CF1-120/130-16 x FL	120 - 130	M16 X 400 X 4	✓	✓	
CF1-0500-16 x FL	126 - 133	M16 X 400 X 4	✓	✓	
CF1-0520-16 x FL	130 - 137	M16 X 400 X 4	✓	✓	
CF1-0590-16 x FL	145 - 152	M16 X 400 X 4	✓	✓	
CF1-0600-16 x FL	151 - 158	M16 X 400 X 4	✓	✓	
CF1-160/170-16 x FL	160 - 170	M16 X 400 X 4	✓	✓	✓
CF1-0663-16 x FL	167 - 174	M16 X 400 X 4	✓	✓	✓
CF1-175/185-16 x FL	175 - 185	M16 X 400 X 4	✓	✓	✓
CF1-0745-16 x FL	189 - 196	M16 X 400 X 4	✓	✓	✓
CF1-195/205-16 x FL	195 - 205	M16 X 400 X 4	✓	✓	✓
CF1-0800-16 x FL	202 - 212	M16 X 400 X 4	✓	✓	✓



Flange off take neck length from top of skin to bolting face of flange, 3" (DN80) & 4" (DN100) & 6" (DN150) = 100mm. Other Flanges available e.g. Tadle E

Example for Part No. DN100 DICL (OD 122) with 100mm Table D flange = CF1-120/130-16 x 100TD

CF FLANGED CLAMPS TWO & THREE PART

PART NO	RANGE	Size, Length, Bolts	FL Drilled "D"		
			3"	4"	6"
			80mm	100mm	150mm
CF2-215/230-16 x FL	215 - 230	M16 X 400 X 8	✓	✓	✓
CF2-230/250-16 x FL	230 - 250	M16 X 400 X 8	✓	✓	✓
CF2-250/270-16 x FL	250 - 270	M16 X 400 X 10	✓	✓	✓
CF2-270/290-16 x FL	270 - 290	M16 X 400 X 10	✓	✓	✓
CF2-290/310-16 x FL	290 - 310	M16 X 400 X 10	✓	✓	✓
CF2-310/330-16 x FL	310 - 330	M16 X 400 X 10	✓	✓	✓
CF2-330/350-16 x FL	330 - 350	M16 X 400 X 10	✓	✓	✓
CF2-350/370-16 x FL	350 - 370	M16 X 400 X 10	✓	✓	✓
CF2-370/390-16 x FL	370 - 390	M16 X 400 X 10	✓	✓	✓
CF2-390/410-16 x FL	390 - 410	M16 X 400 X 10	✓	✓	✓
CF2-410/430-16 x FL	410 - 430	M16 X 400 X 10	✓	✓	✓
CF2-420/440-16 x FL	420 - 440	M16 X 400 X 10	✓	✓	✓
CF2-440/460-16 x FL	440 - 460	M16 X 400 X 10	✓	✓	✓
CF2-450/470-16 x FL	450 - 470	M16 X 400 X 10	✓	✓	✓
CF2-470/490-16 x FL	470 - 490	M16 X 400 X 10	✓	✓	✓
CF2-480/500-16 x FL	480 - 500	M16 X 400 X 10	✓	✓	✓
CF2-490/510-16 x FL	490 - 510	M16 X 400 X 10	✓	✓	✓
CF2-510/530-16 x FL	510 - 530	M16 X 400 X 10	✓	✓	✓
CF2-530/550-16 x FL	510 - 530	M16 X 400 X 10	✓	✓	✓
CF2-550/570-16 x FL	550 - 570	M16 X 400 X 10	✓	✓	✓
CF3-490/520-16 x FL	490 - 520	M16 X 400 X 15	✓	✓	✓
CF3-520/550-16 x FL	520 - 550	M16 X 400 X 15	✓	✓	✓
CF3-550/580-16 x FL	520 - 550	M16 X 400 X 15	✓	✓	✓
CF3-580/610-16 x FL	580 - 610	M16 X 400 X 15	✓	✓	✓
CF3-620/650-16 x FL	620 - 650	M16 X 400 X 15	✓	✓	✓
CF3-650/680-16 x FL	650 - 680	M16 X 400 X 15	✓	✓	✓
CF3-690/715-16 x FL	690 - 720	M16 X 400 X 15	✓	✓	✓
CF3-720/750-16 x FL	720 - 750	M16 X 400 X 15	✓	✓	✓
CF3-750/780-16 x FL	750 - 780	M16 X 400 X 15	✓	✓	✓
CF3-780/810-16 X FL	780 - 810	M16 X 400 X 15	✓	✓	✓



Flange off take neck length from top of skin to bolting face of flange, 3" (DN80) & 4" (DN100) & 6" (DN150) = 100mm. 8" (DN200) & 10" (DN250) = 130mm (Min. Clamp Width 600mm),

Other Flanges available e.g. Tadle E

Example for Part No. DN300 DICL (OD345) with 150mm Table D flange = CF2-330/350-16 x 150TD